## SCREEN CHANNEL SUBWOOFER SYSTEM

## C-218-A





The C-218-A houses two K.C.S. S-1846 18" Ø woofer. These are extra-long excursion cone drivers featuring 4" Ø coils, massive magnetic circuitry, and carefully engineered cooling schemes, resulting in high power handling and low power compression. The two speakers are arranged as direct radiators, resulting in a deep and highly linear bass sound.


## **TECHNICAL DATA**


| Frequency range (-10 dB)  | 20 Hz - 500 kHz      |
|---------------------------|----------------------|
| Nominal Impedance         | 4 Ω                  |
| POWER CAPACITY            |                      |
| Continuous Pink Noise (1) | 1,200 W              |
| Continuous Program        | 2,400 W              |
| Sensitivity 1W/1m         | 101 dB S.P.L.        |
| Crossover Frequency       | 80-110 Hz recomended |
| Dimensions (H x W x D)    | 100 x 70 x 72 cm     |
| Net Weigth                | 74 kg                |
| 1000                      |                      |

(1) Based on a 2 hour test using a continuous 6 dB crest factor pink noise signal band-limited according to IEC 268-1 (1985)

## COMPONENTS

| Cabinet         | C-218-A      |
|-----------------|--------------|
| Loudspeaker 18" | 2 x (S-1846) |





SUMINISTROS EKELONIK, S.A.